Notifikovaná osoba č. 1301



TECHNICKÝ A SKÚŠOBNÝ ÚSTAV STAVEBNÝ, n. o.

BUILDING TESTING AND RESEARCH INSTITUTE Studená 3, 821 04 Bratislava, Slovenská republika

Certificate of constancy of performance

1301 - CPR - 0662

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Steel fibres for concrete AUBEX Group I

for structural uses in all types of concrete, mortar or grout.

The product types are in the Annex 1 on the back side of this certificate.

Placed on the market under the name of

Spajic d.o.o. Koroglaska 13, 19300 Negotin Serbia

and produced in the manufacturing plant

Spajic d.o.o. Koroglaska 13, 19300 Negotin Serbia

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 14889-1: 2006

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on 16 December 2010 (under the CPD) and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Bratislava, 16 February 2021

Molinkovaná osobě last

Dipl. Ing. Daša Kozáková Head of Notified Body 1301

Annex 1 of the Certificate 1301 - CPR - 0662

Product types:

Fibers certified for dosage of 20 kg of fibers per meter cube:

Hooked ends steel fibers AUBEX ZS/N, M, I and Z:

Diameters (mm)	0,40	0,45	0,50	0,51	0,52	0,55	0,60	0,65	0,70	0,75
Diameters (mm)	0,80	0,85	0,90	0,95	1,00	1,05	1,1	1,15	1,2	1,25
Lengths (mm)	28	30	32	35	40	45	50	51	52	60

Waved steel fibers AUBEX ZSW/N, M, I and Z:

			,,							
Diameters (mm)	0,40	0,45	0,50	0,51	0,52	0,55	0,60	0,65	0,70	0,75
Diameters (mm)	0,80	0,85	0,90	0,95	1,00	1,05	1,1	1,15	1,2	1,25
Lengths (mm)	30		35	40	4	5	50	55		60

High performance steel fibers AUBEX ZS5//N, M, I and Z:

Diameters (mm)	0,60	0,65	0,70	0,75	0,80	0,85	0,90	0,95	1,00	1,05
Lengths (mm)			50					60		

High performance steel fibers made of tyre cords Aubex SA/M 0.22x13 and Aubex SA/M 0.25x17

Diameters (mm)	0,22	0,25
Lengths (mm)	13	17

Fibers certified for dosage of 15 kg of fibers per meter cube:

High performance steel fibers AUBEX ZS5

Diameters (mm)	1,00
Lengths (mm)	50

Hooked ends steel fibers AUBEX ZS/N

Diameters (mm)	0,	75			
Lengths (mm)	35	50			

